

1

# SPECTRA B300SLH

Permanent Status Beacon  
 G6,35/GY6,35 Halogen bulb  
 IP Rating: IP65  
 Temp: -25°C to +50°C  
 Unit weight: 262g  
 CE

Order code          Voltage  
 B300SLH250B/x 12-250V

Mountings  
 B300RAB001 Right angle bracket  
 B300TMA001 Tube mounting assembly

B300SLH unit is supplied without a bulb  
 Please order correct voltage and wattage

Dimensions : Ø100 x 150mm  
 1.5mm<sup>2</sup> terminals  
 Cable entry: 1 x 5-7mm push through  
 grommet  
 1 x M20 cable entry ( IP65)

x = Lens colour  
 R = Red                  A = Amber  
 B = Blue                C = Clear  
 G = Green              Y = Yellow

Bulb Type G6,35 / GY6,35

E2S Part No.	Version
BJC20W12VCL	12V 20W
BJC20W24VCL	24V 20W
BJC25W120VCL	115V 25W
BJC25W230VCL	230V 25W

Tel : +44 (0)2 8743 8880 Fax : +44 (0)20 8740 4200  
 mail : sales@e2s.com web : www.e2s.com



2



**ATTENTION:** Installation must be carried out by an electrician in compliance with the latest codes and regulations.



**ATTENTION:** Disconnect from power source before installation or service to prevent electric shock.



**ATTENTION:** Lens on unit will be hot allow to cool prior to removal.



**ATTENTION:** Do not touch the surface of halogen bulb when changing



# A SPECTRA B300SLH

