

1

SPECTRA B400SLF

Permanent Status Beacon
E14 Filament bulb
IP Rating: IP65
Temp: -25°C to +50°C
Unit weight: 510g
CE

Order code Voltage
B400SLF250B/x 12-250V

Mountings
B400RAB001 Right angle bracket
B400TMA001 Tube mounting assembly

B400SLF unit is supplied without a bulb
Please order correct voltage and wattage

Dimensions : Ø140 x 225mm
1.5mm² terminals
Cable entry: 1 x 5-7mm push through
grommet
2 x M20 cable entry (IP65)

x = Lens colour

R = Red	A = Amber
B = Blue	C = Clear
G = Green	Y = Yellow

Bulb Type E14

E2S Part No.	Version
BG351240E	12V 40W
BG352440E	24V 40W
B457513040E	115V 40W
B457523040E	230V 40W

Tel : +44 (0)20 8743 8880 Fax : +44 (0)20 8740 4200
mail : sales@e2s.com web : www.e2s.com



2



ATTENTION: Installation must be carried out by an electrician in compliance with the latest codes and regulations.



ATTENTION: Disconnect from power source before installation or service to prevent electric shock.



ATTENTION: Lens on unit will be hot
allow to cool prior to removal.



A



MOUNTING OPTIONS		
a	STANDARD BASE	
b	POLE MOUNT	B400TMA001
c	90° BRACKET	B400RAB001



C



 Bulb
Not Supplied
Select Correct
Voltage & Wattage

